Innovators of Spraying and Fogging Technology Since 1947







Optional Float Valve

The float valve gives continuous flow capabilities without refilling the tank. For use in areas where large space spraying is required. Several units can be hooked together, using one main water and/or chemical supply source.



HURRICANE

Electric Portable Aerosol Applicator (ULV / Mister)

Dispenses BOTH Oil and Water-based Products

The Hurricane is capable of dispensing disinfectants, deodorizers, germicides and insecticides. It is being used successfully in hospitals, restaurants, warehouses, nursing homes, schools, greenhouses and other institutions. With an adjustable output of 0-5 gallons per hour, this versatile unit gives you the power to handle both large and small area, wherever aerosol particle chemical treatment is needed.

Model 2790 Hurricane 110 Volt **Model 2792 Hurricane 220 Volt** Model 2738 Hurricane w/float 110 Volt Model 2739 Hurricane w/float 220 Volt

SPECIFICATIONS

Adjustable flow rates:	0-5 gal/hr, or 0-19 liters/hr.
Particle size:	5-50 microns (MMD)
Tank capacity:	1 gallon (3.8 liters).
Length:	13 in or 33 cm.
Width:	8 in or 20.3 cm
Height:	14 in or 35.6 cm
Weight (Empty):	6.6 lbs. or 3 kg

INPUT POWER:

Models 2790, 2738: 110/120 volt AC, 6.5 Amps, 50/60 Hz Models 2792, 2739: 220/240 volt AC, 3.5 Amps, 50/60 Hz

SHIPPING DATA:

L x W x H: 15 x 10 x 17 (in) or 38.1 x 25.1 x 43.1 (cm)

Weight: 9 lbs. or 4 kg

Volume: 1.47 Cu. Ft or 0.042 cu. M.

Weight with optional float tank: 10 lbs. (4.54 kg)

DISTRIBUTED BY:

CALL FOR YOUR NEAREST DISTRIBUTOR

317.896.2561 317.896.3788 FAX INFO@DYNAFOG.COM

